



## **20' ISO Container Handling Unit ContiLift CHU 20-25**

**for the economic & safe handling (loading/unloading) of 20' ISO Containers  
with a max. weight of 25 tons. Made of high-tensile steel !**

### **Technical Specification:**

Max. Lifting Capacities: 25 tons (also available with **18 tons/30 tons & 35 tons**)

Overall Length: 7,558 mm \* Overall Width: 2,550 mm \* Overall Height: 4,000 mm

Length of Container/Flat Rack etc.: Max. 6,058 mm

Tare Weight: approx. 3,200 kg

Lifting Angle: 18°

Integrated Spreader for 20' ISO Containers

240 l Hydraulic Oil Tank

Required Piston Hydraulic Pump: 60 l/min./Max. Working Pressure: 300 bar

Pressure Relief Valves/Connecting Pipes 3/4"/Danfoss Distributor, Lever Controls & Radio Spools

Hydraulic Cylinders with Double Plating & High Resistance (proven by Salt Spray Test)

Hydraulically Operated Rear Roll Stabilizer

2 x Foldable Rear Roller Bearings with Twist Locks & 2 x Frontal Twist Locks

High Pressure Filters/Sliding Cart Cylinders/Clamping Basket Cylinders/Rotating Arm Cylinders/

Telescopic Arm Cylinders/Tipping Cylinder & Stabilizing Cylinders

Radio Remote Control/Emergency Solenoid/Security Devices

Coating (2 x Epoxy Bi-Component) on your demand - acc. to RAL-List

Warranty: 1 year on hydraulic components and on structural parts

Installation, Operation & Maintenance Manual in English language

CE Certificate acc. to EU Machine Directive 2006/42/CE

Designed by EOS-ENVIRO & assembled by our contractual manufacturer in Italy/EU

**Option:** Tilting/Dumping Function

We retain the right of technical alterations without prior notice.

Status: January 2016

**No. 89, 6F, Chingdong St., 70144 Tainan/Taiwan ROC \* Website: [www.eos-enviro.com](http://www.eos-enviro.com)**

**Ph.: +886 6 7873 708 \* Cell Phone: +886 9 3334 6753**

**Business No. 28980981 \* Registered as Im- & Exporter by MOEA/BOFT**

**Email: [eos@eos-enviro.com](mailto:eos@eos-enviro.com)**