



EOS-ENVIRO 20' ISO Container Handling Unit ContiLift CHU 20-25 / Mounting Kit

**for the economic & safe handling (loading/unloading) of 20' ISO Containers
with a max. weight of 25 tons. Made of high-tensile steel !**

Technical Specification:

Max. Lifting Capacities: 25 tons (also available with **18 tons/30 tons & 35 tons**)
Overall Length: 7,558 mm * Overall Width: 2,550 mm * Overall Height: 4,000 mm
Length of Container/Flat Rack etc.: Max. 6,058 mm
Tare Weight: approx. 3,200 kg
Lifting Angle: 18°
Integrated Spreader for 20' ISO Containers
240 l Hydraulic Oil Tank
Required Piston Hydraulic Pump: 60 l/min./Max. Working Pressure: 300 bar
Pressure Relief Valves/Connecting Pipes 3/4"/Danfoss Distributor, Lever Controls & Radio Spools
Hydraulic Cylinders with Double Plating & High Resistance (proven by Salt Spray Test)
Hydraulically Operated Rear Roll Stabilizer
2 x Foldable Rear Roller Bearings with Twist Locks & 2 x Frontal Twist Locks
High Pressure Filters/Sliding Cart Cylinders/Clamping Basket Cylinders/Rotating Arm Cylinders/
Telescopic Arm Cylinders/Tipping Cylinder & Stabilizing Cylinders
Radio Remote Control/Emergency Solenoid/Security Devices
Coating (2 x Epoxy Bi-Component) on your demand - acc. to RAL-List
Warranty: 1 year on hydraulic components and on structural parts
Installation, Operation & Maintenance Manual in English language
CE Certificate acc. to EU Machine Directive 2006/42/CE
Designed by EOS-ENVIRO & assembled by our contractual manufacturer in Italy/EU

Option: Tilting/Dumping Function

We retain the right of technical alterations without prior notice.

Status: January 2016

**No.89, 6F, Chingdong St., 70144 Tainan/Taiwan ROC * Website: www.eos-enviro.com
Ph.: +886 6 7873 708 * Cell Phone: +886 9 3334 6753
Business No. 28980981 * Registered as Im- & Exporter by MOEA/BOFT
Email: eos@eos-enviro.com**